

TRUE[®] PS900 TREADMILL

PREMIUM FEATURES AND DURABILITY

The TRUE[®] PS900 is a rugged performer designed for durability. This workhorse is driven by a powerful DC motor that delivers TRUE's signature smooth and quiet acceleration, and proven reliability.



CUSHIONED IMPACT

TRUE's patented Soft System[®] offers the most bio-mechanically correct running surface available. Neoprene shock absorbers in the front third of the deck cushion each foot strike, while the back of the deck provides a firmer sensation allowing for a stronger push off with each step.

USER FRIENDLY INTERACTION

The PS900 LCD screen and console include six preset training programs, one-touch quick keys, one touch HRC Cruise Control[™], and the Gerkin Fitness Test. The bright, legible display monitors every aspect of your workout, including Speed, Incline, Elapsed Time, Distance, Pace, Time Remaining, METs and Calories.

TRUE HRC (HEART RATE CONTROL)[™]

The PS900 is equipped with a digital contact heart rate monitoring system as well as a Polar[®] wireless telemetry system to assist users in maintaining their optimum heart rate and maximizing workout results. One touch HRC Cruise Control is also included, which allows the user to "lock in" on a specific target heart rate. Once the target is set, TRUE HRC Cruise Control will adjust speed and incline automatically throughout the duration of the workout to maintain the targeted heart rate (operates just like the Cruise Control in your car).

BUILT TO LAST

The PS900 is built on a welded steel frame that carries a lifetime warranty. The motor and all other quality components are covered for three years, and labor costs carry a full one year warranty from the date of purchase.



TRUE[®] PS900

TREADMILL

| | | |
|-------------------------|------------------------------------------------|-------------------------------------------------------------------------------------------------------------|
| DRIVE SYSTEM | Drive Motor | TRUE 4hp DC |
| | Incline Motor | Elevation Motor with 1000 lbs of Thrust |
| | Speed Sensor | Magnetic Reed Sensor |
| | Power Source | 115 Volt/15 Amp Dedicated (NEMA 5-15 Power Receptacle) Cord Length 10' (3.0 m) - 220v Option Available |
| EXERCISE SURFACE | Deck | Melamine Laminated 1" Medium Density Fiberboard |
| | Reversible Deck | N/A |
| | Belt | Multi-Ply Polyester Belt with PVC Surface |
| | Rollers | 3" Diameter Crowned Rollers |
| | Impact System | TRUE Soft System (neoprene shock absorbers) |
| | Lubrication | TRUE Proprietary Lubricant "Silax" [®] |
| FRAME | Frame | Robotically Welded Heavy-Gauge Steel |
| | Pedestals | Robotically Welded Heavy-Gauge Steel |
| | Handrails | Flared Protective Dipped Foam Handrails |
| | Medical Handrails | N/A |
| CONSOLE | Display Type | 7" Single Window LCD |
| | iPod [®] Compatibility | N/A |
| | Entertainment Capabilities | Optional External Controller and Screen |
| | Communications | CSAFE Power |
| | Key Type | Membrane/Mechanical Hinge |
| | Command Keys | Express, HRC Cruise Control [®] |
| | Data Readouts | Speed, Incline, Elapsed Time, Time Remaining, Distance, Pace, Heart Rate, Target Heart Rate, METs, Calories |
| Diagnostics | YES | |
| HEART RATE | Contact Heart Rate Monitoring | YES |
| | Wireless Heart Rate Monitoring | Wireless - Polar [®] Compatible |
| | HRC (Heart Rate Control) [®] Workouts | 1 Target HRC |
| | HRC Cruise Control [™] | YES |
| PROGRAMMING | Workouts | 6 Preset, 2 Custom |
| | Fitness Tests | Gerkin Protocol |
| OTHER FEATURES | Accessories | Water Bottle Holder, Key Tray |
| | Safety | Safety Clip Equipped, Extended Handrails, Large Straddle Covers |
| | Balance Bar Control Pad | N/A |
| | Personal Cooling System | N/A |
| PHYSICAL SPECIFICATIONS | Footprint | 82.5"L x 35.5"W (210 cm x 90 cm) |
| | Running Surface | 60"L x 22"W (153 cm x 55 cm) |
| | Machine Weight / Shipping Weight | 303 lbs (137 kg) / 376 lbs (171 kg) |
| | Maximum User Weight | 350 lbs (159 kg) |
| | Decline Option | N/A |
| | Incline Range | 0 to 15% |
| | Speed Range | 0.5-12 mph (0.8-19 kph) |
| | Step-Up Height | 6.25" (16 cm) |
| | Portability | Front Transport Wheels |
| | Regulatory Approvals | UL, CSA, CE for 220V |
| WARRANTY | Warranty | Frame Life, Motor 3 Yrs, Parts 3 Yrs, Labor 1 Yr |

*Specifications subject to change without notice